



**Specifications Ledvance LED  
Downlight Alu DN200 25W 2250lm  
100D - 830 Warm White | 215mm -  
IP44**

[View Product](#)

## General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 233339                              |
| EAN                      | 4058075091498                       |
| manufacturer_code        | 4058075091498                       |
| Brand                    | Ledvance                            |
| Manufacturer Name        | DL ALU DN200 25W/3000K WT IP44 LEDV |
| Any Lamp all-in warranty | 5 Years                             |
| Average Lifetime (h)     | 50000                               |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x26              |
| Wattage                     | 25W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                         |                                       |
|-------------------------|---------------------------------------|
| Light Colour Options    | Single Color                          |
| Driver Included         | Yes                                   |
| Beam Angle (degree)     | 100                                   |
| Luminous Flux (Lumen)   | 2250lm                                |
| Lumen per watt          | 90                                    |
| Power factor            | >0.90                                 |
| Installation Depth (mm) | 120                                   |
| Unified Glare Rating    | < 28 - for hallways and storage rooms |
| Optical Cover           | PMMA (Polymethyl methacrylate)        |
| Suitable for Outdoor    | No                                    |
| Product Type Category   | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-Rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +45                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | DOWNLIGHT ALU                 |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 61  |
| Diameter (mm) | 215 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

